

# **DIFFERENTIAL**

### **FULL SYNTHETIC GL-5 75w90**

Professional Series Full Synthetic GL-5 75w90 is formulated with limited slip additives eliminating the need for the addition of aftermarket limited slip additives. This is the ultimate gear oil providing maximum protection for all gear sets as well as helping to improve fuel economy while promoting longer gear life. This formulation is rated MT-1 and is excellent for manual transmissions requiring a GL-4 rated Synchromesh additive system.

Professional Series Full Synthetic GL-5 75w90 is a 100% synthetic base oil product coupled with a robust additive system and improved viscosity modifier. It provides a high viscosity index low pour-point, reduced friction, fuel savings, better low temperature start-up protection and longer life than most conventional gear oils.



Professional Series Full Synthetic GL-5 75w90 This superior gear oil is formulated to meet the requirements of the American Petroleum Institute's (API) Service Classification FL-5 and MT-1: MIL-PRF-2105E; SAE J-2360: Dana Corp. (including Eaton Axles); Eaton 750,000 mile warranty coverage and 500,000 mile oil drain interval Capabilities; General Electric D 50E9C; (P&H) 474; Mack Truck GO-J Plus; Arvin Meritor, and Rockwell Axles including the International 0-76-E.

## PERFORMANCE APPLICATION CHART

GL-1 MT-1 M2C119A
GL-2/3 Mil-PRF-2105E M2C154A
GL-4 Mack GO-J Outboards and Stern Drives
GL-5 Mack GO\_J Plus

# TYPICAL INSPECTION DATA

JAL Oldde	7 3 00 7 0
API Gravity:	34.0
Viscosity cSt:	
@ 40 C	80.0
@ 100 C	14.5
Brookfield Vis:	<120,000
Vis Index:	180
Flash Point C:	210°C
Pour Point C:	-45°C

#### **SPECIFICATIONS:**

Product No.: PS65089
Net Weight: 960z (2.83 L)
Case Quantity: 4 each

