



Safety Data Sheet - according to: 1907/2006 EC (REACH), 1272/2008/EC (CLP), GHS rev5

## Section 1 - Identification

**Product Identifier:** DOT3 Brake Fluid

**Supplier Phone:** (215) 234-3085

**Supplier:** Professional Series, LLC

**Emergency Phone & Hours:** (215) 234-3085 24 hrs, 7 days/week

**Supplier Address:** 375 Ivyland Rd, Suite 8  
Warminster, PA 18974  
USA

**Intended Use** Industrial Lubricant for use in enclosed systems.

**Uses To Avoid** Applications that generate oil mists in air.

## Section 2 - Hazard Identification

**Signal Word:** WARNING

Other than flammability, no specific data exists for this mixture. Hazard classifications are calculated based on component information.

**Hazard Classifications:**

**Substance Or Mixture** Mixture

Eye damage/irritation (Category 2B), Aspiration Hazard (Category 2), Skin Corrosion/Irritation (Category 3),

**Hazard Statements based on component information:**

**HAZARDS:** Eye contact causes mild eye irritation.  
mild skin irritation.

May be harmful if swallowed and enters airways. Skin contact causes

**Precautions:**

Before handling, put on eye protection, chemical resistant gloves, and cover all exposed skin. Do not allow inhalation of this material to occur. Use only with good ventilation or wear NIOSH approved organics respirator.

**Pictograms:**

(Area to right is blank if no pictograms apply)



**Other Hazards Not Resulting In Classification:** May be hazardous to soil dwelling organisms.

**Summary:** Read entire SDS prior to use. Observe all precautions. Use engineering controls to minimize human exposure to workplace chemicals.



### Section 3 - Composition / Information on Ingredients

		DOT3 Brake Fluid		Page 2
Component	CAS Number	% Range	Exact percentages and component identities are being withheld as trade secrets. Occupational Exposure Levels, Toxicity, and Ecological information on components is shown in Sections 8, 11, and 12 below. Users should read and understand the entire SDS. More specific information on components will be released to medical professionals in case of emergency.	
GLYCOL ETHER MIXTURE	MIXTURE	60 - 100		

### Section 4 - First Aid Measures:

First responders should wear clothing appropriate for industrial exposure in accordance with local codes. At a minimum, all exposed skin should be covered, and latex gloves and eye protection meeting ANSI Z87 or CSA Z94.3 should be worn. First responders should avoid contact with spilled material. Spills of this material present a slip hazard. If smoke, fumes, or airborne mist is present, first responders should use organics respirator or self contained breathing apparatus.

**IF SWALLOWED:** Get immediate medical attention. Call poison control center.

**IF INHALED:** Remove affected person to fresh air and make comfortable for breathing. Get immediate medical attention.

**IF IN EYES:** Remove contact lenses and rinse eyes with cool water. Get immediate medical attention.

**IF ON SKIN:** Rinse affected area with cool water. Get immediate medical attention.

**IF ON CLOTHES:** Do not allow skin contact with contaminated clothing. Remove contaminated clothing and wash before re-use.

**IF EXPOSED:** Contact physician if you feel unwell.

**Most Important Symptoms** ACUTE: Respiratory effects, vision effects. DELAYED: Dermatological effects.

**Indication of Immediate Medical Attention** Difficulty breathing, dizziness, extreme drowsiness, eye irritation, loss of vision, skin rash.

**Section 5 - Fire Fighting Measures:**

DOT3 Brake Fluid

Page 3

**Appropriate Extinguishing Media** Avoid spraying water jet on burning hydrocarbon liquids as this may spread the fire. Use dry chemical or foam extinguishing media.

**Specific Fire Hazards** Fire fighters must be protected from smoke with self contained breathing apparatus. Heavy smoke may obscure vision. Smoke may contain oxides of carbon, nitrogen, sulfur, and chlorine.

**Special Protective Actions** Use water spray to cool exposed containers.

---

**Section 6- Accidental Release Measures:****Personal Precautions**

Spills present a slip hazard. Extinguish/disconnect possible sources of ignition near spill. Ensure adequate ventilation of fumes from affected area. Remove unnecessary personnel from area around spill. Prior to cleaning up, don protective gear including chemical and hydrocarbon resistant outer layer, latex or rubber gloves, rubber boots, and eye protection. Emergency responders should wear chemical and hydrocarbon resistant gear.

**Environmental Precautions**

Small spills may be wiped up with rags. For spills >10 litres- if possible to safely do so, contain the spilled material using diatomaceous earth and/or absorbent pads. Dike drains and prevent material from entering sewers, ditches, drains, or water courses. Place absorbed material into sealed storage containers and consult an environmental expert for proper disposal measures. Immediately report any discharges that escape containment to the local environmental authority or fire department.

**Methods for Cleaning Up**

Absorption with diatomaceous earth and/or absorbent pads is best. Do not use vacuum. Do not wash hydrocarbon or chemical spills away into sewers or drains. Use proper disposal methods for spent absorbents and contaminated rags or clothing.

---

**Section 7- Storage and Handling:****Precautions for Handling**

Read and understand entire Safety Data Sheet prior to handling. Wear all appropriate protective gear prior to handling. Do not allow untrained personnel to handle this product. Handle with care to avoid spillage.

**Methods for Safe Storage**

Store only in original containers. Store containers indoors away from heat and flames. Store in secure location with good ventilation. Keep container sealed when not transferring product. Protect from rain and extreme cold. Avoid storage of hydrocarbons near strong mineral acids or materials marked 'Oxidizer'.

---



## Safety Data Sheet - according to: 1907/2006 EC (REACH), 1272/2008/EC (CLP), GHS rev5

### Section 8- Exposure Controls/Personal Protection:

#### Control Parameters

DOT3 Brake Fluid

Page 4

No exposure limits are established for this mixture. Users should use lowest exposure value shown for components in this section.

#### Component Information - Occupational Exposure Limits:

GLYCOL ETHER MIXTURE

STEL: 6 mg/m<sup>3</sup> TWA: 2mg/m<sup>3</sup> WEEL: 10 mg/m<sup>3</sup>

#### Personal Protective Gear

Eye/Face Protection: ANSI Z87.1-1989 ; Gloves: Latex or Neoprene; Workers should wear safety glasses, gloves, long sleeves, long pants, hair covering, and oil resistant shoes, when handling this product.

#### Engineering Controls

Engineering controls should ensure adequate ventilation to keep airborne concentrations below threshold values shown above. Pumps and handling equipment should be designed to reduce human exposure potentials to liquids being transferred from containers into closed systems.

---

### Section 9- Physical Properties:

<b>Appearance</b>	Clear to Hazy Liquid	<b>Upper Explosive Limit</b>	Not Determined
<b>Odor</b>	Low Indescript	<b>Lower Explosive Limit</b>	Not Determined
<b>Odor Threshold</b>	No Data Available	<b>Vapour Pressure</b>	Negligible
<b>pH</b>	N/A oil based	<b>Vapour Density</b>	>1 (air=1)
<b>Melting Point</b>	Liquid under intended use conditions	<b>Relative Density</b>	0.8-0.9 kg/l 60C
<b>Freezing Point</b>	0 to -20	<b>Solubility</b>	Hydrocarbons, Alcohols
<b>Initial Boiling Point</b>	No Data Available	<b>Partition Coefficient</b>	Log KOW > 4 (mineral oil data)
<b>Boiling Range</b>	313C - 432C	<b>Auto Ignition Temp</b>	Not Determined
<b>Flash Point</b>	>93C	<b>Decomposition Temp</b>	Not Determined
<b>Evaporation Rate</b>	<1 (n-butyl acetate =1)	<b>Viscosity cSt 40C</b>	<14.5 cSt 40C

---

## Section 10- Physical Properties:

<b>Reactivity</b>	May react violently if combined with strong oxidizers and heat.
<b>Chemical Stability</b>	Stable under recommended storage conditions.
<b>Conditions to Avoid</b>	Keep away from fire, sparks, and other sources of ignition.
<b>Possibly Hazardous Reactions</b>	None known.
<b>Incompatible Materials</b>	Strong acids and materials marked 'Oxidizer'.
<b>Hazardous Decomposition Products</b>	Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of nitrogen, and heavy, acrid smoke.

## Section 11- Toxicological Information:

### Symptoms of Exposure:

<b>Likely Routes of Exposure</b>	Dermal and/or Eye exposure from handling. Intended use of product is within enclosed systems which do not generate mist in air.
<b>Ingestion</b>	Ingestion of minimal amounts, e.g. failure to wash hands before eating/smoking, is unlikely to cause symptoms. Swallowing of liquid product may cause vomiting and nausea.
<b>Inhalation</b>	No symptoms are expected under intended use conditions. Exposure to concentrated fumes may cause transient hypoxia.
<b>Dermal/Eye</b>	Minimally irritating by dermal exposure. Eye exposure may cause transient stinging and blurred vision.
<b>Immediate or Delayed Effects</b>	Not expected from exposure to mineral or vegetable oils.
<b>Interactive Effects</b>	None Known

Numerical Measures of Toxicity - components (all LD/LC/EC 50 values shown below are based on animal or fish data)

**Acute Oral Toxicity:** GLYCOL ETHER MIXTURE: Non Hazardous

**Acute Skin Toxicity:** GLYCOL ETHER MIXTURE: Non Hazardous

**Acute Toxicity Inhalation** GLYCOL ETHER MIXTURE: No Data Available



## Section 11- Toxicological Information: (continued)

DOT3 Brake Fluid

Page 6

**Skin Corrosion:** GLYCOL ETHER MIXTURE: GHS Cat. 2 Skin Irritant

**Eye Corrosion:** GLYCOL ETHER MIXTURE: Cat 2A Serious Irritation

**Respiratory Sensitization:** GLYCOL ETHER MIXTURE: No Data Available

**Skin Sensitization:** GLYCOL ETHER MIXTURE: Non Sensitizing

**Germ Cell Mutagenicity:** GLYCOL ETHER MIXTURE: No Data Available

**Carcinogen:** GLYCOL ETHER MIXTURE: No Hazard

**Reproductive Effects:** GLYCOL ETHER MIXTURE: No Data Available

**Section 11- Toxicological Information: (continued)**

**Target Organ  
1 Exposure:** GLYCOL ETHER MIXTURE: No Hazard

**Target Organ  
Multiple  
Exposure:** GLYCOL ETHER MIXTURE: No Hazard

**Aspiration  
Hazard:** GLYCOL ETHER MIXTURE: Cat 2 Aspiration Hazard

**Other Information** No Other Information Available.

---

**Section 12- Ecological Information:**

**Ecological Summary** Hydrocarbon mineral oils, and non-petroleum oils, have low toxicity and are inherently biodegradable. See specific information below regarding aquatic toxicity data on components.

**Bioaccumulation** Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and have low bioaccumulation potential. Specific information on components is shown below.

**Persistence & Degradability** Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and are not persistent. OECD 301 values range from 50% to 95% in 28 days.

**Waste Treatment Effects** Product residues are not expected to enter publicly operated treatment works. No negative effects of this mixture are known.

**Soil Mobility** Mineral oils have been shown to adhere strongly to soil. Mobility is expected to be low.

**Other Adverse Effects** None Known

**Toxicity to aquatic organisms, component information:**

**Aquatic  
Toxicity,  
Acute:** GLYCOL ETHER MIXTURE: Non Toxic

**Safety Data Sheet - according to: 1907/2006 EC (REACH), 1272/2008/EC (CLP), GHS rev5**

DOT3 Brake Fluid

Page 8

**Aquatic  
Toxicity, Long  
Term:**

GLYCOL ETHER MIXTURE: No Chronic Aquatic Toxicity

**Ozone:** This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by 40 CFR 82, Subpt. A, App.A + 8.**Section 13- Disposal Considerations:**

<b>Disposal Containers &amp; Methods</b>	Unused material is not a RCRA hazardous waste. Mixture with other wastes may cause classification as hazardous waste. Users must determine compliance with local, state, and federal regulations for proper classification and disposal of used oils and mixtures thereof. Suitable containers include steel and polyethylene drums and totes, for containment of used oil. Secondary containment is advised. Containers should be kept sealed and protected from rain and exposure.
<b>Physical Chemical Properties Affecting Disposal</b>	Changes in physical and chemical properties during use, such as contamination with lead, zinc, or other metals, may affect classification for disposal. Used oils should be tested to determine metals content and applicable local, state, and federal regulations governing disposal of such fluids.
<b>Improper Disposal</b>	Discharging of oily wastes into any sewer, watercourse, or unregulated drain is discouraged as improper and may result in fines, penalties, cleanup costs, and criminal liabilities for responsible parties.
<b>Precautions for Landfill</b>	Oily liquid should not be disposed in a landfill. Disposal of oily absorbents, rags, or other items into a landfill should only be done with proper permission from local, state, and federal authorities.

**Section 14- Transport Information:****US DOT 49 CFR Parts 171-180:**

<b>Proper Shipping Name</b>	Not Regulated	<b>UN/ID/NA Number:</b>	NA nonregulated
<b>Transport Hazard Class</b>	NA	<b>Packing Group</b>	NA
<b>Labels:</b>	NA	<b>ERG Code</b>	NA
<b>Marine Pollutant:</b>	No		

**IATA-DGR****IATA Proper Shipping Name** Not Regulated**UN/ID Number** NA nonregulated

<b>IATA Class</b>	NA	<b>IATA Packing Group:</b>	NA	<b>IATA Labels</b>	NA
-------------------	----	----------------------------	----	--------------------	----

**IMDG-CODE**

<b>IMDG Proper Shipping Name</b>	Not Regulated		
<b>IMDG UN/ID Number</b>	NA nonregulated	<b>IMDG Shipping Class</b>	NA
<b>IMDG Labels</b>	NA	<b>IMDG Packing Group</b>	NA
		<b>IMDG Marine Pollutant:</b>	No

**MARPOL 73/78 Annex II****MARPOL** Not available for sale in bulk marine shipments**Special Precautions** None





## Section 15- Regulatory Information:

**TSCA Inventory:** All Components are properly registered

**SARA 313 EHS** No Extremely Hazardous Substances in this product

**SARA 311/312 Acute Health Hazard** No

**SARA 311/312 Chronic Health Hazard** No

**SARA 311/312 Fire Hazard** No

**SARA 311/312 Sudden Release of Pressure** No

**SARA 311/312 Reactivity Hazard** No

**CAProp65** This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65.

**REACH :** All components are included in the REACH registry.

**Canada WHMIS Hazard Class:** Not Classified Hazardous

### Other Regulations

Canada WHMIS - No hazard class

---

## Section 16- Other Information:

**Revision Date** 8/1/2016

**Reasons For Revision** Initial GHS SDS preparation.

**Sec 16 Other Info** This Safety Data Sheet was prepared in good faith from the most recent information available, in accordance with ST-SG-AC10-30-Rev5e. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.