

75W90 SYNTHETIC GEAR OIL WITH LIMITED SLIP

Provides superior lubrication and protection for gears. Is a synthetic (Polyalphaolefin) API GL-5 rated gear oil blended to SAE 75W-90 viscosity. It satisfies all requirements for posi-traction and limited slip hypoid gears. Formulated for unsurpassed durability by providing improved seal conditioning, quieter operation and dependable protection. Its unique EP package provides the best in protection against pitting, scoring and wear. Formulated to meet the requirements of the American Petroleum Institute's (API) Service Classification GL-1, GL-2/3, GL-4, GL-5 and MT-1; MIL-PRF-2105E; SAE J-2360: Dana Corp., Mack Truck GO-J, outboards and stern drives



FEATURES AND BENEFITS:

- Fully Synthetic, PAO-based formula. An A.P.I. GL-5-rated gear lubricant formulated to SAE 75W-90.
- Helps prevent wear, pitting and corrosion.
- Excellent shear stability and fluidity in extreme high or low temperatures.
- Allows longer drain life with a shear-resistant formula.



Directions: Differential Fluid Exchange

Service: Apply parking brake and hook up differential fluid exchange machine. Follow operating instructions from equipment manufacturer. Pour entire contents of bottle into machine and start service.

SPECIFICATIONS:

Product No.: PS65076

Net Weight: 64oz (1.89 L)

Case Quantity: 8 each

