

Professional Series Full Synthetic GL-5 75w140 is a superior, high performance, full synthetic, multi-purpose automotive gear lubricant formulated to excel in severe-duty applications. Because of its robust additive system, the use of 100% synthetic base stocks and its scientifically improved shear-stable viscosity modifier it will give extended-service life protection in a multitude of severe duty applications and operating conditions including cold weather. The advanced engineering of this formula will provide excellent protection against wear, corrosion and thermal oxidative degradation and is formulated with limited slip additives eliminating the need for addition of aftermarket limited slip additive. Its unique EP package provides the best in protection against pitting, scoring and wear and is formulated to meet the requirements of the American Petroleum Institute's (API) Service Classification GL-5, MT-1, Mil-PRF-2105E; SAE J-260: Dana Corp. and Mack Truck GO-J



75w140 PERFORMANCE APPLICATION

| | | |
|--------|----------------|----------------------------|
| GL-1 | MT-1 | M2C119A |
| GL-2/3 | Mil-PRF-2105E | M2C154A |
| GL-4 | Mack GO-J | Outboards and Stern Drives |
| GL-5 | Mack GO_J Plus | |

TYPICAL INSPECTION DATA

| | |
|-----------------|----------|
| SAE Grade | 75w140 |
| API Gravity: | 34.0 |
| Viscosity cSt: | |
| @ 40 C | 175.0 |
| @ 100 C | 27.0 |
| Brookfield Vis: | <120,000 |
| Vis Index: | 180 |
| Flash Point C: | 210 °C |
| Pour Point C: | -45 °C |

SPECIFICATIONS:

Product No.: PS65106
Net Weight: 64oz (1.89 L)
Case Quantity: 6 each

