



Safety Data Sheet - according to: 1907/2006 EC (REACH), 1272/2008/EC (CLP), GHS ST_SG_AC10_30_Rev7e

Section 1 - Identification

Product Identifier: AMBER POWER STEERING SERVICE

Supplier: Professional Series, LLC.

Supplier Phone: (215) 234-3085

Supplier Address: 375 Ivyland Road, Suite 8
Warminster, PA 18974

Formula Number 5420

In Case of Spills or Medical Emergency:

24 HRS, 7 DAYS

Intended Use Industrial or Automotive Commercial Uses Only. Not for general household use.

North American Shipments: 1-800-424-9300 or
1-703-527-3887
(CHEMTREC)

Uses To Avoid Non-industrial uses

International Shipments: (215) 234-3085

Section 2 - Hazard Identification

Signal Word: WARNING

Other than flammability, no specific data exists for this mixture. Hazard classifications are calculated based on component information, according to GHS protocols for the relevant hazard.

Hazard Classifications:

Substance Or Mixture Mixture

Eye damage/irritation (Category 2B),

Hazard Statements based on component information:

HAZARDS: Causes eye irritation.

Precautions:

Always protect against possible inhalation of this material. Wear protective gloves, clothing, eye & face protection. Always use with good local ventilation.

NO
PICTOGRAMS
APPLY

Other Hazards Not Resulting In Classification: May be hazardous to soil dwelling organisms.

Summary: Read entire SDS prior to use. Observe all precautions. Use engineering controls to minimize human exposure to workplace chemicals.

Section 3 - Composition / Information on Ingredients

	FN	5420	ACTS AMBER POWER STEERING SERVICE
	CAS Number		% Range
HYDROCRACKED PARAFFINIC MINERAL OIL	64742-55-8		60 - 100
ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL	MIXTURE		5 - 15

Exact percentages and component identities are being withheld as trade secrets. Occupational Exposure Levels, Toxicity, and Ecological information on components is shown in Sections 8, 11, and 12 below. Users should read and understand the entire SDS. More specific information on components will be released to medical professionals in case of emergency.

Section 4 - First Aid Measures:

First responders should wear clothing appropriate for industrial exposure in accordance with local codes. At a minimum, all exposed skin should be covered, and latex gloves and eye protection meeting ANSI Z87 or CSA Z94.3 should be worn. First responders should avoid contact with spilled material. Spills of this material present a slip hazard. If smoke, fumes, or airborne mist is present, first responders should use organics respirator or self contained breathing apparatus.

IF SWALLOWED: Get immediate medical attention. Call poison control center.

IF INHALED: Remove affected person to fresh air and make comfortable for breathing. Get immediate medical attention.

IF IN EYES: Rinse eyes with water. Get immediate medical attention if irritation persists.

IF ON SKIN: Wash skin with cool water.

IF ON CLOTHES: Do not allow skin contact with contaminated clothing. Remove contaminated clothing and wash before re-use.

IF EXPOSED: Contact physician if you feel unwell.

Most Important Symptoms ACUTE: Respiratory effects, vision effects. DELAYED: Dermatological effects.

Indication of Immediate Medical Attention Difficulty breathing, dizziness, extreme drowsiness, eye irritation, loss of vision, skin rash.

Section 5 - Fire Fighting Measures:

Flash Point:	>93C
---------------------	----------------

Hazardous Decomposition Products

Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of nitrogen, and heavy, acrid smoke.

Appropriate Extinguishing Media

Avoid spraying water jet on burning hydrocarbon liquids as this may spread the fire. Use dry chemical or foam extinguishing media.

Specific Fire Hazards

Fire fighters must be protected from smoke with self contained breathing apparatus. Heavy smoke may obscure vision. Smoke may contain oxides of carbon, nitrogen, sulfur, and chlorine.

Special Protective Actions

Use water spray to cool exposed containers.

Section 6- Accidental Release Measures:

Personal Precautions

Spills present a slip hazard. Extinguish/disconnect possible sources of ignition near spill. Ensure adequate ventilation of fumes from affected area. Remove unnecessary personnel from area around spill. Prior to cleaning up, don protective gear including chemical and hydrocarbon resistant outer layer, latex or rubber gloves, rubber boots, and eye protection. Emergency responders should wear chemical and hydrocarbon resistant gear.

Environmental Precautions

Small spills may be wiped up with rags. For spills >10 litres- if possible to safely do so, contain the spilled material using diatomaceous earth and/or absorbent pads. Dike drains and prevent material from entering sewers, ditches, drains, or water courses. Place absorbed material into sealed storage containers and consult an environmental expert for proper disposal measures. Immediately report any discharges that escape containment to the local environmental authority or fire department.

Methods for Cleaning Up

Absorption with diatomaceous earth and/or absorbent pads is best. Do not use vacuum. Do not wash hydrocarbon or chemical spills away into sewers or drains. Use proper disposal methods for spent absorbents and contaminated rags or clothing.

Section 7- Storage and Handling:

Precautions for Handling

Read and understand entire Safety Data Sheet prior to handling. Wear all appropriate protective gear listed in section 2 above prior to handling. Handle with care to avoid spillage.

Methods for Safe Storage

Store only in original containers. Store containers indoors away from heat and flames. Store in secure location with good ventilation. Keep container sealed when not transferring product. Protect from rain and extreme cold. Avoid storage of hydrocarbons near strong mineral acids or materials marked 'Oxidizer'.

Section 8- Exposure Controls/Personal Protection:

ACTS AMBER POWER STEERING
SERVICE

Control Parameters

No exposure limits are established for this mixture. Users should use lowest exposure value shown for components in this section.

Component Information - Occupational Exposure Limits:

HYDROCRACKED PARAFFINIC MINERAL OIL	US ACGIH: TWA: 5 mg/m ³ , STEL: 10 mg/m ³ (as Oil Mist, if generated); US OSHA: 5 mg/m ³ TWA as Oil Mist, if
ALKYLAMINE HYDROCARBYL SULFIDE IN	No Known Hazard

Personal Protective Gear

Eye/Face Protection: ANSI Z87.1-1989 ; Gloves: Latex or Neoprene.

Engineering Controls

Engineering controls should ensure adequate ventilation to keep airborne concentrations below threshold values shown above. Pumps and handling equipment should be designed to reduce human exposure potentials to liquids being transferred from containers into closed systems.

Section 9- Physical Properties

Appearance	Clear to Hazy Liquid	Upper Explosive Limit	Not Determined
Odor	Low Indescript	Lower Explosive Limit	Not Determined
Odor Threshold	No Data Available	Vapour Pressure	Negligible
pH	N/A oil based	Vapour Density	>1 (air=1)
Melting Point	Liquid under intended use conditions	Relative Density	0.8-0.9 kg/l 60C
Freezing Point	0 to -20	Solubility	Hydrocarbons, Alcohols
Initial Boiling Point	No Data Available	Partition Coefficient	Log KOW > 4 (mineral oil data)
Boiling Range	313C - 432C	Auto Ignition Temp	Not Determined
Flash Point	>93C	Decomposition Temp	Not Determined
Evaporation Rate	<1 (n-butyl acetate =1)	Viscosity cSt 40C	>20.5 cSt 40C

ACTS AMBER POWER STEERING
SERVICE

Section 10- Physical Properties:

Reactivity	May react violently if combined with strong oxidizers and heat.
Chemical Stability	Stable under recommended storage conditions.
Conditions to Avoid	Keep away from fire, sparks, and other sources of ignition.
Possibly Hazardous Reactions	None known.
Incompatible Materials	Strong acids and materials marked 'Oxidizer'.
Hazardous Decomposition Products	Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of nitrogen, and heavy, acrid smoke.

Section 11- Toxicological Information:

Symptoms of Exposure:

Likely Routes of Exposure	Dermal and/or Eye exposure from handling. Intended use of product is within enclosed systems which do not generate mist in air.
Ingestion	Ingestion of minimal amounts, e.g. failure to wash hands before eating/smoking, is unlikely to cause symptoms. Swallowing of liquid product may cause vomiting and nausea.
Inhalation	No symptoms are expected under intended use conditions. Exposure to concentrated fumes may cause transient hypoxia.
Dermal/Eye	Minimally irritating by dermal exposure. Eye exposure may cause transient stinging and blurred vision.

Immediate or Delayed Effects Not expected from exposure to mineral or vegetable oils.

Interactive Effects None Known

Numerical Measures of Toxicity - components (all LD/LC/EC 50 values shown below are based on animal or fish data) at max range value section 3.

Acute Oral Toxicity: HYDROCRACKED PARAFFINIC MINERAL OIL: LD50 5001 mg/Kg; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Acute Skin Toxicity: HYDROCRACKED PARAFFINIC MINERAL OIL: LD50 5001 mg/Kg; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Acute Toxicity Inhalation HYDROCRACKED PARAFFINIC MINERAL OIL: Non Hazardous; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

ACTS AMBER POWER STEERING
SERVICE**Section 11- Toxicological Information: (continued)**

Skin Corrosion: HYDROCRACKED PARAFFINIC MINERAL OIL: Non Irritating; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Eye Corrosion: HYDROCRACKED PARAFFINIC MINERAL OIL: Non-Categorized, Suspected Eye Irritant; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL: Non-Categorized, Suspected Eye Irritant

Respiratory Sensitization: HYDROCRACKED PARAFFINIC MINERAL OIL: Non Sensitizing; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Skin Sensitization: HYDROCRACKED PARAFFINIC MINERAL OIL: ; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL: Cat 1 Sensitizer

Germ Cell Mutagenicity: HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Carcinogen: HYDROCRACKED PARAFFINIC MINERAL OIL: No Hazard; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Reproductive Effects: HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Section 11- Toxicological Information: (continued)

ACTS AMBER POWER STEERING
SERVICE

Target Organ 1 Exposure: HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Target Organ Multiple Exposure: HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Aspiration Hazard: HYDROCRACKED PARAFFINIC MINERAL OIL: Cat 1 Aspiration Hazard; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Other Information No Other Information Available.

Section 12- Ecological Information:

Ecological Summary	Hydrocarbon mineral oils, and non-petroleum oils, have low toxicity and are inherently biodegradable. See specific information below regarding aquatic toxicity data on components.
Bioaccumulation	Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and have low bioaccumulation potential. Specific information on components is shown below.
Persistence & Degradability	Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and are not persistent. OECD 301 values range from 50% to 95% in 28 days.
Waste Treatment Effects	Product residues are not expected to enter publicly operated treatment works. No negative effects of this mixture are known.
Soil Mobility	Mineral oils have been shown to adhere strongly to soil. Mobility is expected to be low.
Other Adverse Effects	None Known

Toxicity to aquatic organisms, component information:

Aquatic Toxicity, Acute: HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Volatile Organic Content:

Aquatic Toxicity, Long Term: HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; ALKYLAMINE HYDROCARBYL SULFIDE IN MINERAL OIL:

Ozone: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by 40 CFR 82, Subpt. A, App.A + 8.

Section 13- Disposal Considerations:

Disposal Containers & Methods	Unused material is not a RCRA hazardous waste. Mixture with other wastes may cause classification as hazardous waste. Users must determine compliance with local, state, and federal regulations for proper classification and disposal of used oils and mixtures thereof. Suitable containers include steel and polyethylene drums and totes, for containment of used oil. Secondary containment is advised. Containers should be kept sealed and protected from rain and exposure.
Physical Chemical Properties Affecting Disposal	Changes in physical and chemical properties during use, such as contamination with lead, zinc, or other metals, may affect classification for disposal. Used oils should be tested to determine metals content and applicable local, state, and federal regulations governing disposal of such fluids.
Improper Disposal	Discharging of oily wastes into any sewer, watercourse, or unregulated drain is discouraged as improper and may result in fines, penalties, cleanup costs, and criminal liabilities for responsible parties.
Precautions for Landfill	Oily liquid should not be disposed in a landfill. Disposal of oily absorbents, rags, or other items into a landfill should only be done with proper permission from local, state, and federal authorities.

Section 14- Transport Information:

US DOT 49 CFR Parts 171-180:

Proper Shipping Name: Not Regulated

Combustible Liquid Exemption: N/A

UN/ID/NA Number: NA

Transport Hazard Class NA **Packing Group** NA **Labels:** NA **ERGCode** NA

Marine Pollutant: No

IATA-DGR

IATA Proper Shipping Name NA **UN/ID Number** NA

IATA Class NA **IATA Packing Group:** NA **IATA Labels** NA

IMDG-CODE

IMDG Proper Shipping Name NA

IMDG UN/ID Number NA **IMDG Shipping Class** NA **IMDG Packing Group** NA

IMDG Labels NA **IMDG Marine Pollutant:** No

MARPOL Not available for sale in bulk marine shipments

MARPOL 73/78 Annex II

Special Precautions None

ACTS AMBER POWER STEERING
SERVICE

Section 15- Regulatory Information:

NOTE: Information provided in this section reflects the best available information from suppliers of components used to manufacture this mixture, as of the date of this revision shown below.

OSHA 1910.1200 Hazardous Chemical: Hazards are classified as reported in Section 2 above.

SARA 302 EHS No Known Hazard or Not Listed

SARA 311/312 Acute Yes Chronic No Fire No Pressure No Reactivity No

SARA 313 EHS No Known Hazard or Not Listed

TSCA Status: All Components are properly registered

US State Lists & Regulations:

CA Prop 65 This product contains substances known to the State of California to cause developmental effects: Sulfur dioxide; based on CA 65 List as of August 2018.

US State Right To Know Information:

IL RTK: Petroleum Distillate, CAS 64742-53-6;;

MA RTK: Petroleum Distillate, CAS 64742-53-6;;

MN RTK:

NJ RTK: Petroleum Distillate, CAS 64742-53-6;;

NY RTK:

PA RTK: Petroleum Distillate, CAS 64742-53-6;;

RI RTK: Nothing Listed

Safe Drinking Water Act: No Known Hazard or Not Listed

Canada WHMIS No Known Hazard or Not Listed
Hazard Class:

International Chemical Inventory Status:

Australia AICS

Japan ENCS

Korea ECL

Canada DSL

China IECSC

Europe EINECS

Phillipines PICCS

Canada NDSL

Europe ELINCS

New Zealand Inv

REACH : All components are included in the REACH registry.

Other Regulations



Safety Data Sheet - according to: 1907/2006 EC (REACH), 1272/2008/EC (CLP), GHS ST_SG_AC10_30_Rev7e

ACTS AMBER POWER STEERING
SERVICE

Section 16- Other Information:

Revision Date 7/30/2021

Reasons For Revision New Information From Supplier GHS

Sec 16 Other Info This Safety Data Sheet was prepared in good faith from the most recent information available, in accordance with ST/SG/AC.10/30/Rev.6. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.