

# Section 1 - Identification Product Identifier: AT FLUID ENHANCER

Supplier: Professional Series, LLC. Supplier Phone: (215) 234-3085

Supplier Address: 375 Ivyland Road, Suite 8 Formula Number 4924

Warminster, PA 18974

In Case of Spills or Medical Emergency:

North American 24 HRS, 7 DAYS

Intended Use Industrial Lubricant for use in enclosed systems.

1-800-424-9300 or 1-703-527-3887

Uses To Avoid Non-industrial uses International (CHEMTREC)

Shipments: (215) 234-3085

Section 2 - Hazard Identification

Signal Word: WARNING

Substance Or Mixture Mixture

Other than flammability, no specific data exists for this mixture. Hazard classifications are calculated

based on component information, according to GHS protocols for the relevant hazard.

Shipments:

Eye damage/irritation (Category 2B),

Hazard Statements based on component information:

HAZARDS: Causes eye irritation.

**Hazard Classifications:** 

#### **Precautions:**

Always protect against possible inhalation of this material. Wear protective gloves, clothing, eye & face protection. Always use with good local ventilation.

NO PICTOGRAMS APPLY

Other Hazards Not Resulting In Classification: May be hazardous to soil dwelling organisms.

Summary: Read entire SDS prior to use. Observe all precautions. Use engineering controls to minimize human exposure

to workplace chemicals.



Page 2

	ACTS AT FLUID ENHANCER		
Section 3 - Composition / Information on Ingredients	FN 4924		
	CAS Number	% Range	
HYDROCRACKED PARAFFINIC MINERAL OIL	64742-55-8	60 - 100	Exact percentages
AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS)	MIXTURE	5-15	and component identities are being
HYDROCARBON POLYMER	MIXTURE	<1	witheld as trade secrets. Occupational Exposure Levels, Toxicity, and Ecological information on components is shown in Sections 8, 11, and 12 below. Users should read and understand the entire SDS. More specific information on components will be released to medical professionals in case of emergency.

#### **Section 4 - First Aid Measures:**

First responders should wear clothing appropriate for industrial exposure in accordance with local codes. At a minimum, all exposed skin should be covered, and latex gloves and eye protection meeting ANSI Z87 or CSA Z94.3 should be worn. First responders should avoid contact with spilled material. Spills of this material present a slip hazard. If smoke, fumes, or airborne mist is present, first responders should use organics respirator or self contained breathing apparatus.

IF SWALLOWED: Get immediate medical attention. Call poison control center.

IF INHALED: Remove affected person to fresh air and make comfortable for breathing. Get immediate medical attention.

IF IN EYES: Rinse eyes with water. Get immediate medical attention if irritation persists.

IF ON SKIN: Wash skin with cool water.

IF ON CLOTHES: Do not allow skin contact with contaminated clothing. Remove contaminated clothing and wash before re-use.

IF EXPOSED: Contact physician if you feel unwell.

Most Important Symptoms ACUTE: Respiratory effects, vision effects. DELAYED: Dermatological effects.

Indication of Immediate Difficulty breathing, dizziness, extreme drowsiness, eye irritation, loss of vision, skin rash. Medical Attention



Page 3

**ACTS AT FLUID ENHANCER** 

# **Section 5 - Fire Fighting Measures:**

Flash Point: >93C

Hazardous Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of

Decomposition Products nitrogen, and heavy, acrid smoke.

Appropriate Avoid spraying water jet on burning hydrocarbon liquids as this may spread the fire. Use dry chemical

Extinguishing Media or foam extinguishing media.

Specific Fire Hazards Fire fighters must be protected from smoke with self contained breathing apparatus. Heavy smoke may

obscure vision. Smoke may contain oxides of carbon, nitrogen, sulfur, and chlorine.

# **Section 6- Accidental Release Measures:**

#### **Personal Precautions**

Spills present a slip hazard. Extinguish/disconnect possible sources of ignition near spill. Ensure adequate ventilation of fumes from affected area. Remove unneccesary personnel from area around spill. Prior to cleaning up, don protective gear including chemical and hydrocarbon resistant outer layer, latex or rubber gloves, rubber boots, and eye protection. Emergency responders should wear chemical and hydrocarbon resistant gear.

#### **Environmental Precautions**

Small spills may be wiped up with rags. For spills >10 litres- if possible to safely do so, contain the spilled material using diatomaceous earth and/or absorbent pads. Dike drains and prevent material from entering sewers, ditches, drains, or water courses. Place absorbed material into sealed storage containers and consult an environmental expert for proper disposal measures. Immediately report any discharges that escape containment to the local environmental authority or fire department.

#### **Methods for Cleaning Up**

Absorption with diatomaceous earth and/or absorbent pads is best. Do not use vacuum. Do not wash hydrocarbon or chemical spills away into sewers or drains. Use proper disposal methods for spent absorbents and contaminated rags or clothing.

# **Section 7- Storage and Handling:**

# **Precautions for Handling**

Read and understand entire Safety Data Sheet prior to handling. Wear all appropriate protective gear listed in section 2 above prior to handling. Handle with care to avoid spillage.

#### Methods for Safe Storage

Store only in original containers. Store containers indoors away from heat and flames. Store in secure location with good ventilation. Keep container sealed when not transferring product. Protect from rain and extreme cold. Avoid storage of hydrocarbons near strong mineral acids or materials marked 'Oxidizer'.



10\_30\_Rev7e Page 4
ACTS AT FLUID ENHANCER

# **Section 8- Exposure Controls/Personal Protection:**

Control Parameters

# **Component Information - Occupational Exposure Limits:**

HYDROCRACKED PARAFFINIC MINERAL OIL US ACGIH: TWA: 5 mg/m3, STEL: 10 mg/m3 (as Oil Mist, if generated); US OSHA: 5 mg/m3 TWA as Oil Mist, if

No exposure limits are established for this mixture. Users should use lowest exposure value shown for components in this section.

AMINE/HYDROCARBON MIXTURE (NON No Known Hazard HYDROCARBON POLYMER No Known Hazard

#### **Personal Protective Gear**

Eye/Face Protection: ANSI Z87.1-1989; Gloves: Latex or Neoprene; Workers should wear safety glasses, gloves, long sleeves, long pants, hair covering, and oil resistant shoes, when handling this product.

## **Engineering Controls**

Engineering controls should ensure adequate ventilation to keep airborne concentrations below threshold values shown above. Pumps and handling equipment should be designed to reduce human exposure potentials to liquids being transferred from containers into closed systems.

# **Section 9- Physical Properties**

Appearance	Clear to Hazy Liquid	Upper Explosive Limit	Not Determined
Odor	Low Indescript	Lower Explosive Limit	Not Determined
Odor Threshold	No Data Available	Vapour Pressure	Negligible
рН	N/A oil based	Vapour Density	>1 (air=1)
Melting Point	Liquid under intended use conditions	Relative Density	0.8-0.9 kg/l 60C
Freezing Point	0 to -20	Solubility	Hydrocarbons, Alcohols
<b>Initial Boiling Point</b>	No Data Available	Partition Coefficient	Log KOW > 4 (mineral oil data)
<b>Boiling Range</b>	313C - 432C	Auto Ignition Temp	Not Determined
Flash Point	>93C	Decomposition Temp	Not Determined
Evaporation Rate	<1 (n-butyl acetate =1)	Viscosity cSt 40C	<14.5 cSt 40C



Page 5

**ACTS AT FLUID ENHANCER** 

# **Section 10- Physical Properties:**

Reactivity May react violently if combined with strong oxidizers and heat.

Chemical Stability Stable under recommended storage conditions.

Conditions to Avoid Keep away from fire, sparks, and other sources of ignition.

Possibly Hazardous Reactions None known.

Incompatible Materials Strong acids and materials marked 'Oxidizer'.

**Hazardous Decomposition** 

**Products** 

Byproducts of combustion include carbon dioxide, carbon monoxide, oxides of sulfur, oxides of

nitrogen, and heavy, acrid smoke.

#### **Section 11- Toxicological Information:**

**Symptoms of Exposure:** 

Likely Routes of Dermal and/or Eye exposure from handling. Intended use of product is within enclosed systems which do not

Exposure generate mist in air.

Ingestion Ingestion of minimal amounts, e.g. failure to wash hands before eating/smoking, is unlikely to cause symptoms.

Swallowing of liquid product may cause vomiting and nausea.

Inhalation No symptoms are expected under intended use conditions. Exposure to concentrated fumes may cause

transient hypoxia.

Dermal/Eye Minimally irritating by dermal exposure. Eye exposure may cause transient stinging and blurred vision.

Immediate or

Not expected from exposure to mineral or vegetable oils.

**Delayed Effects** 

Interactive Effects None Known

Numerical Measures of Toxicity - components (all LD/LC/EC 50 values shown below are based on animal or fish data) at max range value section 3.

Acute Oral Toxicity: HYDROCRACKED PARAFFINIC MINERAL OIL: LD50 5001 mg/kg; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): LD50 2001

mg/Kg; HYDROCARBON POLYMER:

Acute Skin

HYDROCRACKED PARAFFINIC MINERAL OIL: LD50 5001 mg/Kg; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): LD50 2001

Toxicity:

mg/Kg; HYDROCARBON POLYMER:

Acute Toxicity Inhalation HYDROCRACKED PARAFFINIC MINERAL OIL: Non Hazardous; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data

Available; HYDROCARBON POLYMER:



Page 6

ACTS AT FLUID ENHANCER

			_	
Castian	11 Tavica		Information:	/ A A M H A A A /
section	II-IOXICO	OPICAL	iniormalion:	conunueou

Skin Corrosion:	HYDROCRACKED PARAFFINIC MINERAL OIL: Non Irritating; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): Non Irritating; HYDROCARBON POLYMER:
	Eye Corrosion  HYDROCRACKED PARAFFINIC MINERAL OIL: Non-Categorized, Suspected Eye Irritant; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): Non-Categorized, Suspected Eye Irritant; HYDROCARBON POLYMER: Non-Categorized, Suspected Eye Irritant
Respiratory Sensitization:	HYDROCRACKED PARAFFINIC MINERAL OIL: Non Sensitizing; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Dat Available; HYDROCARBON POLYMER:
Skin Sensitization:	HYDROCRACKED PARAFFINIC MINERAL OIL: ; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): Non Sensitizing; HYDROCARBON POLYMER:
Germ Cell Mutagenicity:	HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data Available; HYDROCARBON POLYMER:
Carcinogen:	HYDROCRACKED PARAFFINIC MINERAL OIL: No Hazard; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data Available; HYDROCARBON POLYMER:
Reproductive Effects:	HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data



**ACTS AT FLUID ENHANCER** 

# Section 11- Toxicological Information: (continued)

Target Organ 1 HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data

Exposure: Available; HYDROCARBON POLYMER:

**Target Organ** Multiple

Exposure:

HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data

Available; HYDROCARBON POLYMER:

Aspiration

HYDROCRACKED PARAFFINIC MINERAL OIL: Cat 1 Aspiration Hazard; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No

Hazard: Data Available; HYDROCARBON POLYMER:

Other Information No Other Information Available.

# **Section 12- Ecological Information:**

**Ecological Summary** Hydrocarbon mineral oils, and non-petroleum oils, have low toxicity and are inherently biodegradable. See

specific information below regarding aquatic toxicity data on components.

**Bioaccumulation** Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and have low bioaccumulation potential.

Specific information on components is shown below.

Persistance & Hydrocarbon mineral oils, and non-petroleum oils, are inherently biodegradable and are not persistant. OECD 301

values range from 50% to 95% in 28 days.

Degradability

**Waste Treatment** Product residues are not expected to enter publicly operated treatment works. No negative effects of this mixture **Effects** 

Soil Mobility Mineral oils have been shown to adhere strongly to soil. Mobility is expected to be low.

Other Adverse **None Known** 

**Effects** 

Toxicity to aquatic organisms, component information:

Aquatic HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data Toxicity, Available; HYDROCARBON POLYMER:

Acute:

**Volatile Organic Content:** 



Page 8

**ACTS AT FLUID ENHANCER** 

Aquatic HYDROCRACKED PARAFFINIC MINERAL OIL: No Data Available; AMINE/HYDROCARBON MIXTURE (NON HAZARDOUS): No Data Available; Toxicity, HYDROCARBON POLYMER:
Long
Term:

Ozone

This product neither contains, nor was manufactured with a Class II ODS as defined by 40 CFR 82, Subpt. A, App.A + 8.

# **Section 13- Disposal Considerations:**

as hazardous waste. Users must determine compliance with local, state, and federal regulations for proper classification and disposal of used oils and mixtures thereof. Suitable containers include steel and polyethylene drums and totes, for containment of used oil. Secondary containment is advised.

Containers should be kept sealed and protected from rain and exposure.

**Physical Chemical Properties** 

**Affecting Disposal** 

Changes in physical and chemical properties during use, such as contamination with lead, zinc, or other metals, may affect classification for disposal. Used oils should be tested to determine metals content and applicable local, state, and federal regulations governing disposal of such fluids.

Improper Disposal Discharging of oily wastes into any sewer , watercourse, or unregulated drain is discouraged

as improper and may result in fines, penalties, cleanup costs, and criminal liabilitites for

responsible parties.

Precautions for Landfill Oily liquid should not be disposed in a landfill. Disposal of oily absorbents, rags, or other items into

a landfill should only be done with proper permission from local, state, and federal authorities.

Section 14- Transport Information:

US DOT 49 CFR Parts 171-180:

Proper Shipping Name: Not Regulated

Combustible Liquid N/A Exemption:

UN/ID/NA Number: NA

Transport Hazard Class NA Packing Group NA Labels: NA ERGCode NA

Marine Pollutant: No

IATA-DGR

IATA Proper Shipping Name NA UN/ID Number NA

IATA Class NA IATA Packing Group: NA IATA Labels NA

IMDG-CODE

IMDG Proper Shipping Name NA

IMDG UN/ID Number NA IMDG Shipping Class NA IMDG Packing Group NA

IMDG Labels NA IMDG Marine Pollutant: No

MARPOL Not available for sale in bulk marine shipments

MARPOL 73/78 Annex II Special Precautions None



Page 9

#### **ACTS AT FLUID ENHANCER**

# **Section 15- Regulatory Information:**

NOTE: Information provided in this section reflects the best available information from suppliers of components used to manufacture this mixture, as of the date of this revision shown below.

OSHA 1910.1200 Hazardous Chemical: Hazards are classified as reported in Section 2 above.

SARA 302 EHS No Known Hazard or Not Listed

SARA 311/312 Acute Yes Chronic No Fire No Pressure No Reactivity No

SARA 313 EHS No Known Hazard or Not Listed

TSCA Status: All Components are properly registered

**US State Lists & Regulations:** 

CA Prop 65 This product contains substances known to the State of California to cause developmental effects: Ethylene glycol (ingested);

based on CA 65 List as of August 2018.

**US State Right To Know Information:** 

IL RTK: Not Listed;

MA RTK: Not Listed;

MN RTK: Not Listed;

NJ RTK: Not Listed;

NY RTK:

PA RTK: Nothing Listed

RI RTK: Nothing Listed

Safe Drinking Water No Known Hazard or Not Listed

Act:

Canada WHMIS No Known Hazard or Not Listed

**Hazard Class:** 

**International Chemical Inventory Status:** 

Australia AICS Japan ENCS Korea ECL Canada DSL
China IECSC Europe EINECS Phillipines PICCS Canada NDSL

Europe ELINCS New Zealand Inv

REACH: All components are included in the REACH registry.

**Other Regulations** 





**ACTS AT FLUID ENHANCER** 

### **Section 16- Other Information:**

Revision Date 7/30/2021

Reasons For Revision New Information From Supplier GHS

Sec 16 Other Info

This Safety Data Sheet was prepared in good faith from the most recent information available, in accordance with ST/SG/AC.10/30/Rev.6. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.