

Professional Series Full Synthetic GL-5 75w85 is formulated with limited slip additives eliminating the need for the addition of aftermarket limited slip additives. This is the ultimate gear oil providing maximum protection for all gear sets as well as helping to improve fuel economy while promoting longer gear life. This formulation is rated MT-1 and is excellent for manual transmissions requiring a GL-4 rated Synchronmesh additive system.

Professional Series Full Synthetic GL-5 75w85 is a 100% synthetic base oil product coupled with a robust additive system and improved viscosity modifier. It provides a high viscosity index low pour-point, reduced friction, fuel savings, better low temperature start-up protection and longer life than most conventional gear oils.

Professional Series Full Synthetic GL-5 75w85 is formulated to meet the requirements of the American Petroleum Institute's (API) Service Classification GL-5 and MT-1: MIL-PRF-2105E; SAE J-2360.



SPECIFICATIONS:

Product No.: PS65033
Net Weight: 32oz (964mL)
Case Quantity: 12 each

75w85 PERFORMANCE APPLICATION

API GL-5 & MT-1

MIL-L2105E

SAE J2360

BMW/MINI

83 12 0 445 838

83 22 2 295 532

83 22 2 413 511

83 22 2 413 512

Castrol, BOT 448

Hypoid Acel Oil G1/G2/G3

CHRYSLER/DODGE/JEEP

05136035AA

68083381AA

FORD

WSS-M2C942-A

XY-7585-QL

GM

88862826

92184900

SAF Carbon Mod

HONDA/ACURA

09200-9014A

HYPOID GEAR OIL HGO-1

MAZDA

K020-01-SG1

MB

235.15/235.7/235.74

A 001989 59 03

NISSAN/INFINITY

KDL38-75801P

AUDI G 052 513

TOYOTA/LEXUS

08885-02506

08885-02606

08885-81060

GEAR OIL LT/LX

VW/AUDI

G 052 513

TYPICAL INSPECTION DATA

SAE Grade: 75w85
 API Gravity: 34.0
 Viscosity cSt:
 @ 40 C 68.0
 @ 100 C 12.5
 Brookfield Vis: <120,000
 Vis Index: 171
 Flash Point C: 210 °C
 Pour Point C: -45 °C

